

**MATERIAL SAFETY DATA SHEET CHEMTREC**

PRODUCT TRADE NAME: ATLANTIC 15A14 LUBE OIL (ALL ISO GRADES)

EFFECTIVE DATE: JANUARY 1, 2005 PAGE 1 OF 2

THIS MATERIAL SAFETY DATA SHEET CONTAINS ENVIRONMENTAL, HEALTH AND TOXICOLOGY INFORMATION FOR YOUR EMPLOYEES. PLEASE MAKE SURE THIS INFORMATION IS GIVEN TO THEM. IT ALSO CONTAINS INFORMATION TO HELP YOU MEET COMMUNITY RIGHT-TO-KNOW/EMERGENCY RESPONSE REPORTING REQUIREMENTS UNDER SARA TITLE 111 AND MANY OTHER LAWS. IF YOU RESELL THIS PRODUCT, THIS MSDS MUST BE GIVEN TO THE BUYER OR THE INFORMATION INCORPORATED IN YOUR MSDS.

DOT HAZARDOUS CLASSIFICATION: NOT REGULATED GREASE OR OIL -N.O.S.  
NFPA HELATH HAZARD: 1 FLAMMABILITY:1 REACTIVITY: 1 PERSONAL PROTECTION: B

**SECTION 01 - HAZARDOUS INGREDIENTS**

IF PRESENT, IARI, NTP AND OSHA CARCINOGENS AND CHEMICAL SUBJECT TO THIS REPORTING REQUIREMENTS OF SARA TITLE 111, SECTION 313 ARE IDENTIFIED IN THIS SECTION.

CAS NUMBER TLV PEL %

**(NON-HAZARDOUS) COMPONENTS**

PROPRIETARY COMPONENTS: N.J.T.S.R.N.

SYNTHETIC OIL 80100362-5008P 99.9

80100362-50049P 0.5

**SECTION 02 - PHYSICAL DATA**

WATER SOLUBILITY INSOLUBLE BOILING POINT, F N/A

SP, GRAVITY 0.84 MELTING POINT, F N/A

APPEARANCE & COLOR WATER WHITE LIQUID VOLATILE BY VOLUME, % NIL

ODOR MILD ODOR VAPOR PRESSURE N/A

EVAPORATION RATE N/A VAPOR DENSITY N/A

**SECTION 03 - FIRE AND EXPLOSION HAZARDS**

FLASH POINT: (ASTM 092) C.O.C. MIN 290 F UPPER FLAMMABLE LIMIT: N/D LOWER FLAMMABLE LIMIT:

N/D EXTINGUISHING MEDIA: CO2, DRY CHEMICAL FOAM, WATER FOG, FOAM

\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

SPECIAL FIRE FIGHTING PROCEDURES: TREAT AS OIL FIRE; USE SELF-CONTAINED BREATHING APPARATUS.

UNUSUAL FIRE & EXPLOSIVE HAZARDS: NONE

\_\_\_\_\_

## PAGE 2: ATLANTIC 15A14 LUBE OIL (ALL ISO GRADES)

### SECTION 04 - ENVIRONMENTAL AND DISPOSAL INFORMATION

ACTION TO BE TAKEN FOR SPILL/LEAKS: Stop flow, scrape, wipe, mop up, or absorb with diatomaceous earth or inert material. Store in appropriate container for disposal.

DISPOSAL METHOD: disposal should be in compliance with federal, state and local laws.

### SECTION 05 - HEALTH HAZARD DATA

CARCINOGENS: No carcinogens present

ROUTE OF ENTRY: Ingestion

EFFECTS OF OVEREXPOSURE: May cause irritation to eyes and skin on sensitive individuals.

EMERGENCY FIRST AID PROCEDURES:

EYES: Flush with water for at least 15 minutes.

SKIN: Wash with soap and water. See physician if irritation persists.

INHALATION: Remove to fresh air. See physician if irritation persists.

ORAL: Call a physician. Do not induce vomiting. Keep warm.

ADDITIONAL: Prolonged or repeated contact may produce mild skin irritation and inflammation.

Personnel with pre-existing skin disorder should avoid contact.

### SECTION 06 - REACTIVITY DATA

STABILITY: Stable.

INCOMPATIBILITY: Strong oxidizing agents, welding

POLYMERIZATION: Will not occur

THERMAL DECOMPOSITION: Carbon Monoxide, Carbon Dioxide

CONDITIONS TO AVOID: Do not heat above flash point

### SECTION 07 - SPECIAL PROTECTION INFORMATION

**RESPIRATORY PROTECTION: Normally not needed**

GLOVES PROTECTION: Neoprene or nitrile rubber gloves recommended

EYE PROTECTION: Approved safety glasses or goggles

OTHER PROTECTION: Chemically resistant boots and apron recommended

WORK/HYGIENIC PRACTICES: Use standard methods

### SECTION 08 - SPECIAL PRECAUTIONS AND ADDITIONAL INFORMATION

**Avoid storage near open flame or other sources of ignition. Spills may cause slippery floors. Proper footwear required.**

Remove contaminated clothing and laundry before reuse. Wash hands with soap and water before eating, drinking or smoking. Discard contaminated leather gloves and shoes.

The above information is based on the data of which we are aware and believe to be correct as of the date hereof. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar and since data made available subsequent to the date hereof may suggest modification of the information, we do not assume any responsibility for the results of its use. This information is furnished upon condition that the person receiving it shall make his/her own determination of the suitability for his/her particular purpose.

May be used to comply with OSHA's Hazard Communication Standard 29 CFR 1910.1200. Standard must be specific requirements.

N/D - Not determined N/A - Not applicable

< -- Less than. > -- Greater than.