

# ATLANTIC™ 400

## THREAD SEALING COMPOUND

### DESCRIPTION

ATLANTIC 400 is a premium, multi-purpose, non-toxic, non-drying thread sealant and anti-seize compound; formulated with a balanced blend of lubricating solids, rust and corrosion inhibitors, homogenized into a non-melting grease carrier. ATLANTIC 400 is engineered to provide a superior leak-proof seal for the life of the connection, while at the same time maintaining its anti-seize capabilities, allowing easy disassembly without thread damage. ATLANTIC 400 does not contain any solvents, lead, graphite, TFE Polymers, or clay fillers.

### USAGE

ATLANTIC 400 is a dependable, quality sealant for threaded connections on lines carrying numerous types of liquids and gases including water, natural gas, LPG, etc. Found in a wide variety of industries. ATLANTIC 400 provides reliable service on brass, black iron, galvanized stainless steel, aluminum, copper, PVC and fiberglass reinforced pipes.

### ADVANTAGES

M NON-TOXIC    M ECONOMICAL  
M LEAK PROOF SEAL    M NON-MELTING  
M NON DRYING    M PREVENTS CORROSION  
M LUBRICATES THREADS    M EASY APPLICATION

### OPERATING RANGE

Base grease provides lubrication from 15F to 450F. Lubricating solids lubricate to 1800F.(Brushable from 15F).

### TYPICAL SPECIFICATIONS

<u>TEST</u>	<u>ASTM METHOD</u>	<u>RESULT</u>
Color	----	Cream
N.L.G.I. Grade	----	1
Worked Penetration	D-217	310-340
Flash Point, F	D-92	400
Pressure Service Range	----	to 8,000 PSI
Rust Test	D-665	Pass

### PACKAGE AVAILABILITY

½ Pint Brush Top Jar (packaged 12/case)  
1 Pint Brush Top Jar (packaged 12/case)  
1 gal. Pail, 5 gal. Pail, 15 gal. Keg and 55 gal. Drum

**NOTE: CAUTION-NOT RECOMMENDED FOR OXYGEN SERVICE**