

ATLANTIC™ LUBE "O" SEAL VALVE LUBRICANT GRADE

DESCRIPTION

ATLANTIC LUBE "O" SEAL VALVE LUBRICANT GRADE is a totally synthetic, waterproof and chemical resistant lubricant containing *Teflon® that produces a tough durable film between the valve plug and body surfaces to seal, lubricate and reduce operating torque. ATLANTIC LUBE "O" SEAL VALVE LUBRICANT GRADE is also NSF/U.S.D.A. H-1 *Registered which gives a full acceptability in areas where incidental food contact may occur.

USAGE

ATLANTIC LUBE "O" SEAL VALVE LUBRICANT GRADE is available in both stick and bulk form and can be used in most lubricated plug, gate, and ball valves. Applications include valves used in food packaging, drinking water, waste water and sewage treatment plants. The bulk form is excellent for lubrication of valve operators, gears, bearings, stems, threaded connections, etc.

ADVANTAGES

- M Wide Temperature Range
- M USDA H-1 Rated
- M Non-Melting
- M Chemical Resistant
- M Waterproof, Will Not Wash Out

NSF H-1 Registration No. 059315 TYPICAL SPECIFICATIONS

<u>TEST</u>	<u>ASTM METHOD</u>	<u>RESULT</u>
Color	----	Transparent White
Base Type	----	Synthetic
Drop Point, °F	D-566	None
Service Range, °F	----	0 to 400F
Flash Point, °F	D-92	425
Pour Point, °F	D-97	0
Special Additives	----	*Teflon®



PACKAGE AVAILABILITY

5 qt. Can, 5 gal. Pail, 15 gal. Keg
J & K Gun Sticks

