

# ATLANTIC™ No. 2 H.D. PTFE SEALANT AND LUBRICANT

## DESCRIPTION

ATLANTIC No.2 H.D. is a highly versatile valve sealant and lubricant that contains a balanced blend of fine to coarse PTFE particles suspended in a special synthetic lubricating carrier. ATLANTIC No.2 H.D. is resistant to a large variety of line products such as water, crude or heating oils, fuels, dilute acids, steam, dilute caustics, petroleum solvents, butane, propane, L.P.G. odorants, etc.

## USAGE AND APPLICATION

ATLANTIC No.2 H.D. is designed for use on ball or plug valves that are leaking due to wear or scoring. It is excellent as a thread sealant for standard pipe or coarse threads, packing for stuffing boxes, and a supplementary sealant for valve stems. ATLANTIC No.2 H.D. is pumpable with a valve lubricant high pressure (10,000 psi) gun\*\* such as the ATLANTIC 1010 Hand Gun or the ATLANTIC 1699 Hydraulic Hand Gun.

## ADVANTAGES

- M Stop Leaks**
- M Will Not Dry Out**
- M Is Both A Sealant And Lubricant**
- M Broad Serviceability Range**

## TYPICAL SPECIFICATIONS

Color    Reddish Brown  
Texture    Viscous and Granular  
Base Oil and Thickener    Synthetic  
Bridging Agent    PTFE Fluorocarbon Resin  
Service Range    0 F to 500 F  
Service Pressure    15,000 PSI

\*\*Caution: Due to the multiple particle sizes of PTFE do not pump with air operated equipment. Not Recommended for Oxygen service.

## PACKAGE AVAILABILITY

"J" Sticks (1¼ " x 8½) packaged 16 sticks/carton, 3 carton/case