

# ATLANTIC™ TUFF STUFF GREASE

## DESCRIPTION

ATLANTIC TUFF STUFF is a new generation grease designed for today's demanding industries. It represents the "state of the art" in grease technology, combining the finest base oil stocks, additives and synthetic thickeners available to provide a truly multi-service, friction reducing, non-melting grease with unmatched protection in normal and severe service applications.

ATLANTIC TUFF STUFF is a blend of the highest quality paraffinic base oils and polymers coupled with ATLANTIC'S newest proprietary extreme pressure additive which forms a tough durable film of protection from friction, wear and corrosion over a wider temperature range (-20F. to 400F.).

ATLANTIC TUFF STUFF'S unique formulation provides superior adhesion to metal surfaces that does not easily wash off, run out or separate even under adverse conditions of water, steam or dilute chemicals thus providing lower grease consumption and extended lubrication cycles.

## USAGE

ATLANTIC TUFF STUFF provides unmatched performance in a wide variety of conventional and severe service applications found in a diverse range of industrial, marine, mining, construction, agricultural and automotive applications. ATLANTIC TUFF STUFF is recommended for all roller, sleeve and pillow block bearings, bushings, couplings, universal joints, and sliding surfaces where a multi-purpose or extreme pressure grease is required. The use of ATLANTIC TUFF STUFF can allow you to reduce your grease inventory.

## ADVANTAGES

- M Withstands Extreme Pressures
- M Reduces Friction & Wear
- M Wide Temperature Range
- M Will Not Melt or Run Out
- M Excellent Metal Adherence
- M Highly Water Resistant
- M Prevents Rust & Corrosion
- M Reduces Grease Inventories

## TYPICAL SPECIFICATIONS

<u>TEST METHOD</u>	<u>ASTM TEST</u>	<u>RESULTS</u>
N.L.G.I. Grade	-	2
Worked Penetration 60 stokes	D-217	285
10,000 strokes		300
Base Oil Viscosity	D-445	
SUS @ 100°F		1200
SUS @ 210°F		85
Pour Point, °F	D-97	-20
Flash Point, °F	D-92	410
Dropping Point, °F	D-566	None
Corrosion Preventative Test	D-1743	Pass
Timken OK Load, lbs.	D-2509	70

## PACKAGE AVAILABILITY

14 oz. cartridges, 5-gal. Pails, 15-gal. Kegs, 55-gal. Drums